



ZINSSER® ALLCOAT INTERIOR MATT

Primer and finish in one for all interior surfaces

- Multi surface application.
- Ultra durable formula.
- Scuff & scrub resistant†
- Mould & algae resistant coating#
- Streak-free finish.



ZINSSER® ALLCOAT INTERIOR MATT

DESCRIZIONE

ALLCOAT® Interior Matt is an ultimate performance all surface paint. Designed for the long term decoration of timber, metal, masonry, uPVC, concrete, plasterboard, plaster, walls and ceilings.

UTILIZZO CONSIGLIATO

ALLCOAT® Interior Matt is a primer and finish in one for all interior surfaces, with premium properties and performance. This product is designed for the durable finish of wood, metal, masonry, PVC, concrete, drywall, plaster, walls and ceilings. A scrub-resistant, stain-resistant, even matt finish with perfect and uniform covering power. For use on, among others, PVC, ceramic tiles, aluminium, copper, steel, galvanised steel, wood, plasterboard, white plaster, concrete, walls and ceilings in any interior.

SISTEMA CONSIGLIATO

two-coat system - no primer needed

DATI TECNICI

| | |
|------------------------------|-----------|
| Densità: | 1,2 - 1,4 |
| Livello di lucentezza a 60°: | <3% |
| Livello di lucentezza a 85°: | w5% |
| Residuo secco in peso: | 60% |
| Residuo secco in volume: | 50% |
| wet_scrub_resistance: | wsr_c1 |

TEMPI DI ASCIUGATURA A 20°C/UR 50%

| | |
|-------------------------|------------|
| Asciutto al tatto: | 1 hr |
| Asciutto da rivestire: | 2 hrs |
| Completamente indurito: | 5 - 7 days |

CONSUMO TEORICO

10-12m²/litre per coat

CONSUMO PRATICO

In practice, hiding power depends on many factors, such as the porosity and roughness of the substrate and material loss during application.

PREPARAZIONE DELLA SUPERFICIE

Surfaces must be clean, dry, sound and free of dirt, dust, grease, wax, wallcovering adhesive, soap film, loose paint or other surface contamination. Clean surfaces with thoroughly with a proprietary degreaser / cleaner in accordance with the manufacturers instructions. Ensure surface is completely dry before painting, with a maximum moisture content of 16%. Remove all existing mould and mildew before painting using an appropriate mould removal solution. If you are concerned about mould and mildew growth on other surfaces and/or unseen places, contact a mould removal specialist. Follow appropriate guidelines for mould removal. Remove all rust back to clean, bare ferrous metal, if signs of rusting are evident apply an anti-corrosive metal primer in accordance with manufacturers recommendations. Check for satisfactory paint adhesion by cutting an "X" with a razor blade in the old paint film. Apply cellophane tape firmly over the "X" and pull tape quickly away. If old paint releases, remove by scraping. Sand rough areas and remove dust. New/Bare Plaster: For optimum results seal first with a suitable sealer. Special precautions should be taken during surface preparation of pre-1960 paint surfaces as they may contain harmful lead. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Two-coat System – No Priming Required! Seal all stains with an appropriate Zinsser stain blocking primer where required before applying ALLCOAT® Interior Matt.

ISTRUZIONI PER L'USO

Stir thoroughly before use. Apply with a synthetic bristle brush, medium pile roller or sprayer. For airless spraying, use a .017 tip and high medium (2000-2600 PSI) pressure. Apply when air and surface temperatures are between 10°-32°C and humidity is less than 80%.

CONDIZIONI DI APPLICAZIONE

Apply when air and surface temperatures are between 10°-32°C and humidity is less than 80%.

APPLICAZIONE E DILUIZIONE: PENNELLO

Apply with a synthetic bristle brush

APPLICAZIONE E DILUIZIONE: RULLO

Use a medium pile roller

APPLICAZIONE E DILUIZIONE: SPRAY SENZ'ARIA

Tip: .017 / Pressure: 2000-2600 PSI.

PULITURA DELLE ATTREZZATURE / DEGLI SVERSAMENTI

Clean application tools, spatters and spills immediately with warm water and liquid detergent; rinse with water. Follow equipment manufacturer's directions to clean spray equipment. Remove dried ALLCOAT® Interior Matt with a household cleaner; rinse with water. Do not empty into drains or watercourses. Some local authorities have special facilities for the disposal of waste coatings

NOTE

ALLCOAT® Interior Matt can be tinted to all colours via the CS2 tinting system using the appropriate tint base. Multiple containers of tinted paint should be intermixed (boxed) to ensure colour uniformity.

ALLCOAT® Interior Matt is not intended for application to floors or any surface subject to water immersion or prolonged contact including shower enclosures, saunas or steam rooms. If using in areas of high humidity e.g. bathrooms allow at least 24 hours before subjecting the applied coating to humidity from the shower/bath. It is recommended that a trial area is first coated to ensure the product is satisfactory to individual requirements before full surface application

DATI RELATIVI ALLA SICUREZZA

| | |
|--------------------------------|--|
| Livello di COV: | 2 g/L |
| Soluzione premiscelata COV: | 2 g/L |
| Categoria COV: | IIA/a |
| Limite di COV: | 30g/l |
| grenelle: | c |
| Note riguardanti la sicurezza: | Consult the Safety Data Sheet and the safety information on the paint can. |

SCADENZA

At least 2 years from production date in unopened original packaging, if stored in dry, well-ventilated areas, out of direct sunlight, at temperatures between 5 and 32°C.

Data del rilascio: 10/06/2024

Colori e formati di confezione disponibili: Si prega di consultare la pagina relativa al prodotto su www.rust-oleum.eu per una visione complessiva dei colori e dei formati di confezione effettivamente disponibili.

Dichiarazione di non responsabilità: Le informazioni contenute nel presente documento sono al meglio della nostra conoscenza, vere e accurate e sono fornite in buona fede ma senza garanzia. L'utente sarà ritenuto soddisfatto/a indipendentemente dall'idoneità dei nostri prodotti per il suo proprio scopo particolare. In nessun caso Rust-Oleum Europe potrà essere ritenuta responsabile per danni consequenziali o incidentali. I prodotti devono essere conservati, maneggiati e applicati in condizioni conformi alle raccomandazioni dettagliate di Rust-Oleum Europe contenute nella copia più recente della scheda tecnica del prodotto. È responsabilità dell'utente accertarsi di disporre della copia attuale. Le copie più recenti della scheda tecnica del prodotto sono disponibili gratuitamente e scaricabili da www.rust-oleum.eu o a fronte di richiesta al nostro servizio clienti. Rust-Oleum Europe si riserva il diritto di modificare le proprietà dei suoi prodotti senza alcun preavviso.

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T: +31 (0) 165 593 636
F: +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T: +44 (0)1914 113 146
F: +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T: +33(0) 130 40 00 44
F: +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T: +32 (0) 13 460 200
F: +32 (0) 13 460 201
info@rust-oleum.eu