



ZINSSER[®] COVER STAIN[®]

Primer-Sealer Stain Killer

- Fast Drying – recoat in less than 2 hours
- Designed for interior and exterior surfaces
- High hiding formula blocks most stains, including nicotine
- Excellent for sealing water-soluble tannin bleed on cedar and redwood

ZINSSER® COVER STAIN®

POPIS PRODUKTU (DLOUHY)

Multi-applicable solvent-based stain-blocking primer and sealer. Ideal for interior / exterior use. Paintable in only 2 hours. Can be finished with any solvent-based or water-based top coat.

DOPORUČENÉ POUŽITÍ

Recommended for application to fire, smoke and water damaged surfaces, including: interior ceilings, walls, doors, trim, cabinets, furniture and related paintable surfaces.

Exterior siding, fascia, soffits, trim, doors, walls, foundations, railings, and related paintable surfaces that may have been damaged by fire, smoke or water.

Cover Stain is recommended for application to the following fire, smoke or water damaged substrates:

Interior: New or previously painted, cured plaster and cement-based coatings, wood (including pine, fir, cedar, redwood, plywood), metal (including aluminum, iron, steel, and copper), vinyl, PVC, masonry (including stucco, concrete block, poured concrete, and brick).

Exterior: New or previously painted wood (including pine, fir, cedar, redwood, and pressure-treated wood), hard-board, metal (including aluminum, iron, steel and copper), vinyl, PVC.

TECHNICAL DATA

technical_data: 12/13%
technical_data: 74.5%
technical_data: 56.3%

DRY TIMES BY 20

dry_times_by_20: 35 minutes
dry_times_by_20: 2 hours
dry_times_by_20: 4 to 7 days

TEORETICKÁ SPOTŘEBA

9.8 m² per litre

PRAKTICKÁ SPOTŘEBA

Coverage may vary depending upon method of application and surface porosity.

PŘÍPRAVA POVRCHU

Surfaces should be clean, dry, sound and free of dust, dirt, excessive chalky material, grime, grease, oil, wax, mildew, wallpaper, adhesive or any contamination that may interfere with adhesion. If unsure, always wash surface with an appropriate ammoniated cleaning solution or solvent (do not use tri sodium phosphate based cleaners). Remove any peeling and / or unsound coatings. Sand any remaining paint film edges smooth. Lightly sand exposed exterior wood with 80 to 100grit sandpaper to remove loose or weathered wood fibers and mill glaze. When priming over stained areas, first attempt to remove as much of the stain as possible by washing, sanding, scraping, etc. Allow surface to dry completely before priming. Countersink exposed nail heads, spot-prime and fill all nail holes and gouges. Wire brush rusty areas. Spot prime knots and sap streaks with B-I-N Primer-Sealer before whole surface priming with Cover Stain.

NÁVOD K POUŽITÍ

Shake or stir before using. In most cases only one coat is necessary to prime most surfaces. If excessive absorption occurs over very porous substrates a second coat may be necessary. Spot priming is recommended only under high hiding topcoat paints. For best results prime entire surface before painting. Allow to come to room temperature before use. Use in a well ventilated area avoiding high humidity.

PODMÍNKY POUŽITÍ

Apply when air and surface temperatures are between 5°C and 32°C and humidity is less than 85%. Note that temperature and humidity directly affect dry time of the product.

Higher temperatures and lower humidity will accelerate the dry time while lower temperatures and higher humidity will slow down the dry time.

APLIKACE A ŘEDĚNÍ: ŠTĚTEC

Apply with a natural or synthetic bristle brush. Cover Stain is designed to be used without thinning.

APLIKACE A ŘEDĚNÍ: VÁLEČEK

Cover Stain is designed to be used without thinning.

APLIKACE A ŘEDĚNÍ: BEZVZDUCHOVÝ SPREJ

Follow manufacturer's instructions when using spray equipment. Airless spraying- use a 0.015" to 0.017" tip at 1800 to 2200 P.S.I. Cover Stain is designed to be used without thinning.

ČIŠTĚNÍ ZAŘÍZENÍ / ROZLITÍ

Clean up spills and drips with a rag soaked in mineral spirits or paint thinner. If spills or drips have dried, use paint remover. Application tools may be cleaned using paint thinner – rinse tools repeatedly in mineral spirits or paint thinner until solvent runs clear and tool is thoroughly cleaned.

POZNÁMKY

Standard white Cover Stain may be tinted to off white and pastel shades by adding no more than 60 ml. solvent based colorants per 5 liter. Deep Tint may be tinted to mid to dark tones by adding no more than 250 ml per 5 liter.

Cover Stain is not intended for application to floors, decks, roof surfaces or any surfaces subject to immersion or prolonged contact with water

DATA SAFETY DATA

data_safety_data: maximum 350 g/l
data_safety_data: II A/g
data_safety_data: 350 g/l (2010)
data_safety_data: Consult product Safety Data Sheet

DOBA POUŽITELNOSTI

Minimum of 5 years from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 4 and 27°C.

last_updated: 01/10/2024

footer_data_colors_pack_sizes: footer_data_colors_pack_sizes.value

footer_data_disclaimer: footer_data_disclaimer.value

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM s-Hertogenbosch
The Netherlands
T: +31 (0) 165 593 636
F: +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T: +44 (0)1914 113 146
F: +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T: +33(0) 130 40 00 44
F: +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T: +32 (0) 13 460 200
F: +32 (0) 13 460 201
info@rust-oleum.eu