



ZINSSER[®] COVERS UP[™]

Stain blocking primer and finishing coat in one

- Matt white finish, for indoor use
- Primer and finishing coat in one
- Blocks stains from water, nicotine and smoke
- Ideal for retouching a ceiling
- Quick drying and low odour

ZINSSER® COVERS UP™

POPIS PRODUKTU (DLHÝ)

COVERS UP™ is an acrylic, solvent-based stain blocking primer and ceiling paint in one. This low odour and quick drying primer ensures a matt white finish that matches the colour of most ceiling tiles and white ceiling paints. The vertical aerosol is easy to use. Ideal for retouching a ceiling. For indoor use.

ODPORÚČANÉ POUŽITIE

For indoor use. Apply as a primer / finish to interior acoustic ceiling tiles or painted ceilings, light fixtures, HVAC ductwork and vents, overhead pipes and conduit, or anywhere an overhead high hiding stain sealing primer or spot finish is needed. New, primed or previously painted ceiling tiles, drywall, cured plaster, cement, stucco, wood (pine, fir, birch, oak and plywood), aluminum, iron, steel and galvanized metal, PVC, glossy laminates and other interior surfaces.

DRY_TIMES_BY_20

Na dotyk suché: 30 minutes (@ 20°C)
Suchý na opätovné natieranie: 2 hours

TEORETICKÁ SPOTREBA

1.5 m²/aerosol

PRAKTICKÁ VÝDATNOSŤ

Practical coverage depends on many factors such as porosity and roughness of the substrate, type of application and material losses during application

PRIÍPRAVA POVRCHU

Surfaces should be clean, dry, sound and free of dust, dirt, excessive chalky material, grime, grease, oil, wax, mildew, wallpaper adhesive or any contamination that may interfere with adhesion. If unsure, always wash surface with a household ammonia and water solution, appropriate cleaning solution, or solvent (Do not use tri sodium phosphate based cleaners). Remove any unsoundly adhered coatings. Sand any remaining paint film edges smooth with the surface. Attempt to remove existing stains by washing, sanding, scraping, etc.

NÁVOD NA POUŽITIE

Use at room temperature in a well-ventilated area - avoid high humidity. Shake can until ball inside rattles, then continue shaking for one minute. Repeat shaking periodically during use. Test spray pattern on scrap surface before using. Spray 25-30 cm from surface. Apply with short 'dusting' strokes. When finished, clean valve by holding can upside down and spraying until clear gas comes out. To clear clogged spray tip, remove from can and clean with pin.

PODMIENKY APLIKÁCIE

Use at a temperature of 4 - 32°C at a humidity <85%.

ČISTENIE ZARIADENIA / POSTRIEKANIE

Clean spills and drips with a rag dampened in mineral spirits.

POZNÁMKY

COVERS UP™ is not intended for application to floors, decks, roof surfaces or any surface subject to immersion or prolonged contact with water.

DATA_SAFETY_DATA

Kategória VOC: /
Poznámky k bezpečnosti: Consult Safety Data Sheet and Safety Information printed on the aerosol.

SKLADOVATELNOSŤ

Minimum of 3 years from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 5 and 25°C.

last_updated: 04/02/2025

footer_data_colors_pack_sizes: footer_data_colors_pack_sizes.value

footer_data_disclaimer: footer_data_disclaimer.value

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T: +31 (0) 165 593 636
F: +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T: +44 (0)1914 113 146
F: +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T: +33(0) 130 40 00 44
F: +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T: +32 (0) 13 460 200
F: +32 (0) 13 460 201
info@rust-oleum.eu