



ZINSSER[®] GARDZ

Clear, water-based, acrylic resin sealer

- Penetrates deeply into porous surfaces
- Dries fast to a hard, moisture-proof film
- Prevents drywall blistering / bubbling
- Binds down chalky surfaces
- Strengthens soft texture finishes

ZINSSER® GARDZ

DESCRIZIONE

Clear, water-based, acrylic resin sealer

UTILIZZO CONSIGLIATO

Drywall– Gardz prevents bubbles that form when damaged drywall is skim coated with spackling or joint compound. Gardz penetrates and seals damaged facing paper, restoring it to a sound surface for repairs, suitable for painting or wallcovering. New Drywall / Joint Compound and Spackling - New gypsum drywall, joint compound and spackling are very porous and can make finish coatings appear splotchy and uneven. Gardz penetrates and uniformly seals, creating a moisture resistant film that protects drywall from blistering, tearing and other damage when redecorating in the future.

Plaster– Freshly applied plaster is extremely porous but also extremely alkaline with a pH of 12.0 or more in many cases. Allow new plaster to cure at least 24 hours before applying Gardz. Before priming old, bare plaster with Gardz be sure to determine that the surface is clean, dry and in sound condition, taking care to repair any cracks or holes with spackling paste or joint compound before resealing the surface.

Calcimine- Calcimine is a very old form of plaster that is extremely chalky and water-sensitive. Gardz penetrates calcimine more effectively than oil-based coatings and has a much lower odor. Because it resists moisture, Gardz prevents water-based topcoat paint or texture finishes from softening up calcimine layers underneath.

Wallpaper Adhesive Residue - Water-based coatings or texture finishes will reactivate old wallpaper adhesive, resulting in cracking and peeling. Gardz is formulated to completely seal in residual adhesive and prevent it from ruining water-based topcoats and texture finishes. **Texture and Popcorn Finishes** - Use Gardz to seal textured walls and popcorn ceilings before applying water base primer or paint. Gardz penetrates soft or crumbly texture material and hardens it, creating a durable, water resistant barrier that prevents primer or paint from softening texture material underneath.

Old Wallpaper– Most of the wallpaper installed before the 1960's was true paper, with no vinyl coating. To determine if the wallcovering is a true paper wipe a wet sponge across the surface – if the water is readily absorbed it means there is no vinyl coating. This type of wallcovering can be effectively sealed with Gardz. First, peel away any loose or frayed edges – whatever remains should be firmly adhered to the wall. Apply Gardz as you would to any other wall surface.

Pre-Wallcovering Primer– Gardz penetrates, seals, sizes and protects drywall facing paper and skim coat, providing a properly sealed surface for new wallcovering. At redecorating time, Gardz protects the surface of the drywall when the old wallcovering is stripped off. **Builder's Flat Paint** – Gardz penetrates chalky, builder's flat paint and binds it to the wall, providing water-resistant protection from paint, wallcovering and texture finishes.

DATI TECNICI

Densità:	1
Residuo secco in peso:	26%
Residuo secco in volume:	22%

TEMPI DI ASCIUGATURA A 20°C/UR 50%

Asciutto al tatto:	30 minutes
Asciutto da rivestire:	3 hours
Completamente indurito:	3 days

CONSUMO TEORICO

9-11 m²/L/coat

PREPARAZIONE DELLA SUPERFICIE

Surfaces must be clean, dry, sound and free of contamination. Remove loose or peeling paint by sanding or scraping. For best results remove loose wallcovering and residual wallcovering adhesive. Seal stains with a Zinsser stain killing primer sealer. Cut away loose or torn drywall facing paper with a razor or sand back with 80-grit paper until a sound area is reached. If drywall is gouged, remove loose pieces of gypsum core. Skim coated or spackled areas should be sanded smooth using 100 grit sandpaper.

ISTRUZIONI PER L'USO

Stir well before using. Do not thin. Using a brush, medium nap roller or sprayer, apply Gardz liberally to the entire surface to ensure good penetration. Do not over-apply or coating will sag. Gardz appears milky blue-white during application but dries water clear; properly sealed surfaces should have a uniform sheen when viewed at an angle. Reapply to areas that have been missed or not sufficiently coated.

CONDIZIONI DI APPLICAZIONE

>10°C - <32°C, < 85% R.H.

APPLICAZIONE E DILUIZIONE: PENNELLO

For best results use a quality nylon/polyester or other, similar, synthetic blend bristle brush with flagged tips. Do not overload the brush or the product will drip and run on vertical and overhead applications.

APPLICAZIONE E DILUIZIONE: RULLO

Use a roller with a 3 / 8" or less synthetic nap. Apply Gardz to walls from the bottom up to prevent product from running down the wall. If this happens, back-roll or brush out the runs to even out the film. When applying to ceilings do not press hard or the product will drip out of the roller.

APPLICAZIONE E DILUIZIONE: SPRAY SENZ'ARIA

Nozzle: 0.011-0.013 / Pressure: 55 - 83 bar

PULITURA DELLE ATTREZZATURE / DEGLI SVERSAMENTI

Clean up spills and drips with a wet, soapy cloth or rag. Wash application tools in warm, soapy water immediately after use. If product has dried on application tool, soak it overnight in a solution of ammoniated household detergent and water. Follow manufacturer's instructions when cleaning spray equipment.

NOTE

Gardz has a milky-blue colour (that helps to determine where it has been applied) but dries water clear. It is formulated for use directly from the container. Tinting is not recommended.

DATI RELATIVI ALLA SICUREZZA

Livello di COV:	<30 g/L
Note riguardanti la sicurezza:	Consult Safety Data Sheet and Safety Information printed on the can.

SCADENZA

Minimum of 2 years from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 4 and 32°C.

Data del rilascio: 10/06/2024

Colori e formati di confezione disponibili: Si prega di consultare la pagina relativa al prodotto su www.rust-oleum.eu per una visione complessiva dei colori e dei formati di confezione effettivamente disponibili.

Dichiarazione di non responsabilità: Le informazioni contenute nel presente documento sono al meglio della nostra conoscenza, vere e accurate e sono fornite in buona fede ma senza garanzia. L'utente sarà ritenuto soddisfatto/a indipendentemente dall'idoneità dei nostri prodotti per il suo proprio scopo particolare. In nessun caso Rust-Oleum Europe potrà essere ritenuta responsabile per danni consequenziali o incidentali. I prodotti devono essere conservati, maneggiati e applicati in condizioni conformi alle raccomandazioni dettagliate di Rust-Oleum Europe contenute nella copia più recente della scheda tecnica del prodotto. È responsabilità dell'utente accertarsi di disporre della copia attuale. Le copie più recenti della scheda tecnica del prodotto sono disponibili gratuitamente e scaricabili da www.rust-oleum.eu o a fronte di richiesta al nostro servizio clienti. Rust-Oleum Europe si riserva il diritto di modificare le proprietà dei suoi prodotti senza alcun preavviso.

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T : +31 (0) 165 593 636
F : +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T : +44 (0)1914 113 146
F : +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T : +33(0) 130 40 00 44
F : +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T : +32 (0) 13 460 200
F : +32 (0) 13 460 201
info@rust-oleum.eu